



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1855/162/05/24/1141

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD
NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC
DEVELOPMENT ZONE, GAOMI CITY, SHANDONG
CHINA

Description

PPE Type : *protective glove against mechanical risks*

Product reference : LC133302P-HGVL06 / LC133304P-HGVL06

Article code : /

Glove description : LC133302P-HGVL06 - 13 Gauge Red Polyester Liner, with Black Latex Coating, Crinkle Finish Glove
LC133304P-HGVL06 - 13 Gauge Grey Polyester Liner, with Black Latex Coating, Crinkle Finish Glove

Available sizes : 6/XS - 12/XXXL

Pictures :



LC133302P-HGVL06
EN388
CE
SIZE 10/XL 2132X



SHANDONG XINRUIDA LABOR
PROTECTIVE PRODUCTS CO., LTD
NORTH OF WEIJIAO ROAD,
EAST OF KANGCHENG STREET,
ECONOMIC DEVELOPMENT ZONE,
GAOMI CITY, SHANDONG, CHINA



Reference standard :

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

-

EN 388:2016 + A1:2018

2 1 3 2 X

At the date of the certificate, the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the user instructions index 02 dated from May 2024.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
William GELAS
Certification manager



Date of first issue: 29 May 2024
Date of end of validity: 29 May 2029
Date of Update 01 : 29 May 2024



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD

**MANUFACTURER’S TECHNICAL FILE TO THE
PPE REGULATION 2016/425**

Reference of the product	:	LC133302P-HGVL06 / LC133304P-HGVL06
Article code	:	/
Technical file index	:	02
Last update	:	May 2024

IDENTIFICATION

Reference of the product :	:	LC133302P-HGVL06 /
		LC133304P-HGVL06
Article code :	:	/
Basic Model		
Technical file index :	:	02
Last update :	:	May 2024

Manufacturer :

SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD
NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC
DEVELOPMENT ZONE, GAOMI CITY, SHANDONG
CHINA

tel : +86-536-2580591
fax : +86-536-2580591

Factory :

SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD
NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC
DEVELOPMENT ZONE, GAOMI CITY, SHANDONG
CHINA

tel: +86-536-2580591
fax: +86-536-2580591

GLOVE DESCRIPTION

General glove description and intended use:

LC133302P-HGVL06 - 13 Gauge Red Polyester Liner, with Black Latex Coating, Crinkle Finish Glove

LC133304P-HGVL06 - 13 Gauge Grey Polyester Liner, with Black Latex Coating, Crinkle Finish Glove

This glove is designed against mechanical risks.

Type of coating finish : crinkle

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒	☒ Standard ☒ Instruction for use ☒ Marking
§1.4	Manufacturer's instructions and information is available	☒	☒ Standard ☒ Instruction for use ☐ Marking
§2.5	PPE which may be caught up during use	☒	☐ Standard ☒ Instruction for use ☐ Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒	☒ Standard ☒ Instruction for use ☒ Marking
§3.3	The PPE is intended to protect against mechanical injuries	☒	☒ Standard ☒ Instruction for use ☒ Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		Black	Latex			1mm
		grey	Polyester	176 g/m ²	13	
		red	Polyester	176 g/m ²	13	
Back		grey	Polyester	176 g/m ²	13	
		red	Polyester	176 g/m ²	13	
Cuff		grey	Polyester + Elastic	296 g/m ²	13	
		red	Polyester + Elastic	296 g/m ²	13	
Binding		Black	Polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : 5

Available size range: 6/XS - 12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388:2016 + A1:2018

Protection offered	Performance levels
Abrasion resistance	2
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	X
Impact Protection	N/A

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S240301698_1 S210403687_1 S211010448_1 S240301840_1 S191215616_1	
EN 388	S240301698_1 S211010447_1 S2111110630_1 S211111317_1 S240504525_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : LC133302P-HGVL06 / LC133304P-HGVL06

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Marking of packaging example :



Method of marking on the glove :

PRINT LOGO ON THE BACK AND LABEL OF GLOVES

Packaging suitable for transport:

12 PAIRS/ POLYBAG, THEN 120 PAIRS IN THE CARTON.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

First is the incoming quality control, which is very important in purchasing the yarn. This is the primary control point to stop the defective materials into the productive process. Through some physical methods, such as visual, touch, compare with the samples, the best quality of yarns will be choosed for gloves. Second is the in-process quality control. The deployment of latex, the selection of gloves, the make of model, the print on the back of gloves and so on are the inprocess quality control. That means the quality control activities after the storage of materials and before the warehousing of finished goods. And the quality of the testing phase is called final quality control. We select samples randomly and do EN 388 and EN ISO 21420 tests every month, such as abrasion, blade cut, the PH, Azo, etc. Finally is the outgoing quality control. When the goods are finished, the workers will choose the defective goods out. And that will be kept records. The quality record can provide objective evidence about the goods quality.



INSTRUCTIONS FOR USE

SHANDONG XINRUIDA LABOR PROTECTIVE PRODUCTS CO., LTD

NORTH OF WEIJIAO ROAD, EAST OF KANGCHENG STREET, ECONOMIC DEVELOPMENT ZONE,
GAOMI CITY, SHANDONG

CHINA

Glove reference : LC133302P-HGVL06 / LC133304P-HGVL06

Article code: /

User notice index : 02

Last update : May 2024

Glove description :

LC133302P-HGVL06 - 13 Gauge Red Polyester Liner, with Black Latex Coating, Crinkle Finish Glove
LC133304P-HGVL06 - 13 Gauge Grey Polyester Liner, with Black Latex Coating, Crinkle Finish Glove

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: 6/XS - 12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Information about marking

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.



The CE marking means that this product meets the requirements of the regulation 2016/425

Mechanical hazard - EN 388:2016 + A1:2018



2 1 3 2 X

Levels of performance



Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

Read carefully the instructions for use provided with the product

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Contains natural rubber latex, which could cause allergic reactions, including anaphylactic choc.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear...).

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available with product.



LC133302P-HGVL06
EN388
SIZE 10/XL 2132X

SHANDONG XINRUIDA LABOR
PROTECTIVE PRODUCTS CO., LTD
NORTH OF WEIJIAO ROAD,
EAST OF KANGCHENG STREET,
ECONOMIC DEVELOPMENT ZONE,
GAOMI CITY, SHANDONG, CHINA